HD-STREAM

Real-Time Collaboration





HD-Stream enables users to stream live HD images with the touch of a button. Users simply connect to a qualified USB camera and stream in full HD resolution to any device, in any location, without any hassles. The self-contained box is ideal for live collaboration between colleagues, educational instruction, industrial inspection, and more! HD-Stream redefines the way you work.

PLATFORM INDEPENDENT

Stream live HD images simultaneously to PC, MAC, desktops, tablets or phones.

FLEXIBLE

HD-Stream connects directly to a variety of *qualified* USB HD cameras.

IT FRIENDLY

Connects directly to a network via wired Ethernet or Wi-Fi connection. NO additional software downloads or licensing fees required.

SECURE


HIPPA compliant. Encrypted transmission ensures no patient identifiable information is exchanged with transmission of live images.

POWERFUL

Stream to 50 users from one box or connect multiple boxes to stream to larger #'s (i.e. 200).

SIMPLE

User-friendly interface that is designed to be simple and efficient. No training required.



HD-STREAM

Real-Time Collaboration



Real-Time HD Web Streaming: H.264 compressed at 30 fps, 1080p, 720p,

or 360p via Ethernet or WiFi

Minimum Bandwidth Requirement per Client: 1080p (default): 5 MBit/s

720p: 2 MBit/s 360p: 0.5 MBit/s

Remote Viewing Platforms: PC, MAC, Tablet, Desktop, iPad,

iPhone, Android Devices. Uses VLC for

decoding video stream.

Live HD Image Capture: TIFF, JPEG, PNG Formats

Live HD Video Recording (AVI): Up to 200 hours of HD recording. Record,

Play/Pause, First Frame, Last Frame, Step Back/Forward, Time Slider

Auto Naming: Automatically names captured HD files and

videos, as designated.

Print Control: Connect to a printer via USB, WIFI, or Bluetooth

Required Access Ports

(for UDP and TPC transmission): 554, 8080

Streaming Protocols: RTP, RTCP, RTSP, HTTP
Default Streaming Protocol: RTSP on port 554, 8080

HD-Stream Box: Power Button, Speaker/Microphone/Audio Port

Ethernet Port, USB 3.0 Port (x3), USB 2.0 Port (x1)

HDMI Port, Mini DisplayPort Connector

SD Reader, Thunderbolt 3 Port, Key Lock Hole

Electrical: 19V, 120W AC-DC Power Adapter (120V-220V)

Safety & Regulatory Information:

Mounting: Desktop, with VESA Mounting Adapter Included

Dimensions: 8.30" x 4.5" x 1.10" (211 mm x 116 mm x 28 mm)

Operating Temperature: 0° C to 40° C

HD-Stream: Includes: HD-Stream box, power supply, keyboard,

mouse, HDMI to HDMI display cable

*Design and specifications subject to change